



Account Details

Account No. 9036149_USS6_10_10
 Account KENTUCKY ASSOC OF ELEC COOPS
 Address KENTUCKY ASSOC OF ELEC COOPS, 4300 CHAMPIONS TRACE LN, , LOUISVILLE, Kentucky, 40218, United States
 Sales Org. ABB Installation Products USA
 Sales Distribution
 Currency USD
 As on Date 10-19-2023

Catalog No. AL4/0NTN

Product Details

UPC: 783786693689



Details: Tin Plated Aluminum Two-Hole NEMA Lugs - Straight Lug, Concentric 4/0 Stranded AL9CU, Installing Dies TX ,71H, 298, 840, 11A. 2 Stranded - 4/0 Stranded AL-CU use VC-5 or VC-6 Dies. Length 6 inch. Pad 1-3/16 inch wide x 3-11/32 inch long x 5/16 inch thick. Barrel 1-15/16 inch long x 7/8 inch Outside Diameter. (2) 9/16 inch Diameter holes on 1-3/4 inch centers. Oxide Inhibitor. White Cap.

Product Details

Details

| | | | |
|------------------------|-------------------------------|-------------------|---------------|
| Catalog No. | AL4/0NTN | UPC | 783786693689 |
| Description | AL TIN 2HOLE NEMA STR LUG 4/0 | GSA Compliance | No |
| Std. Package Weight | 0.210 LB | Discount Schedule | 92 |
| Product Family | 92B | CCC | |
| Restock Fee | | Currency | USD |
| Customer Reference No. | | Notes | |
| Brand Name | HOMAC | Package Qty. | 50 |
| Minimum Order Qty. | 50 | Country of Origin | United States |

Specifications

General Characteristics

| | |
|------------------|---|
| Category | Wire connectors |
| Type | Compression Lug Two Hole |
| Special Features | Dual Rated for use with Aluminum and Copper Conductors. Prefilled with Oxide Inhibitor. Marked with Conductor Sizes and Die Reference. Meet or Exceed ANSI C119.4 Specifications. UL Listed |
| Application | General Purpose Lugs for Aluminum and Copper Terminations |
| Connection | Compression |
| Material | Aluminum |
| Finish | Tin Plated |
| Insulation | None |

Dimensions and Classifications

| | |
|------------|-------------|
| Brand Name | Homac |
| Wire Size | 4/0 STR AWG |